

# VIGILANT W2000

SPECIFICATION SHEET

## Delivers exceptional performance for client viewing applications

The Vigilant W2000 Series, renowned for its versatility, stands out as a top-tier client viewing station. Engineered with multiple features, it seamlessly integrates into diverse installation environments. This dynamic viewing station supports up to four monitors and is specifically designed for mid-range surveillance projects. Powered by the 13th generation Intel Core processor family, it ushers in a new era of computing with an array of cutting-edge features. Additionally, the Now Micro Engineering Team has pre-integrated DICE Management and Monitoring Software. The DICE Complete solution is focused on technical support needs to drive increased first-call resolution and reduced downtime in the field. Hardware information, logs and location information are embedded in a real-time interface that includes KVM, terminal and file system access tools.



### Key Features



**13th Generation Intel Core Processors**



**Mid Tower Form Factor**



**Supports up to 4 Displays**



**5-year Global Next Business Day Onsite Warranty**



# VIGILANT W2000

## System

### Processor

- 13th Generation Intel i7 Core Processors

### Operating System

- Windows 11 Pro
- Windows 10 IoT

### Displays Supported

- Up to 4 with NVIDIA GPU

### Memory

- Default 16GB DDR5 (2x8GB)
- Upgradeable to 32GB DDR5

### Video Outputs

- Integrated Intel Graphics
- Optional NVIDIA T400 GPU
- Optional NVIDIA T1000 GPU

### I/O Ports

- Rear ports:
- 2x USB 2.0
  - 2x USB 3.2 Type A Gen2
  - 2x USB 3.2 Type A Gen1

### Networking

- 2 x 1GbE LAN Ports

### Security Module

- Trusted Platform Module 2.0v3

### Hardware Monitoring

- Now Micro DICE Enhancements

### Warranty

- 5 Year Global Next Business Day, Onsite Warranty Standard

## Mechanical

### Form Factor

- Precision Tower

### OS Drives

- 256GB SSD

### Storage

- 2TB SATA Data Drive
- Upgradable

### Power Supplies

- Single 500W PSU

### Operating Temperature

- 50°F to 95°F (10°C to 35°C)

### Operating Humidity

- 10 to 80% (non-condensing)

### Dimensions & Weight

- Height – 14.52" (369mm)
- Width – 6.81" (173mm)
- Depth – 16.53" (420mm)
- Weight – 18.74 lbs (8.5 kg)