

because now matters

VIGILANT S5000

SPECIFICATION SHEET

Optimal performance for critical video setups with increased storage requirements

The Vigilant S5000, tailored for enterprise surveillance deployments, excels in managing high camera counts and accommodating large retention requirements. Its robust design ensures reliable performance even in demanding environments. Designed with 24 bays, the Vigilant S5000 has a maximum storage capacity of 480TB. Additionally, the Now Micro Engineering Team has pre-integrated iDRAC Enterprise and DICE Management and Monitoring Software. The DICE Complete solution is focused on technical support needs to drive increased first-call resolution and reduced downtime in the field. Hardware information, logs and location information are embedded in a real-time interface that includes KVM, terminal and file system access tools.









Dual Intel Xeon Scalable Processors



Up to 480TB of raw storage



Standard Redundant Power Supply



iDRAC Enterprise with Now Micro DICE Enhancements



5-year Next Business Day Onsite Warranty









VIGILANT S5000

System

Processor

Dual Intel Xeon Silver 4410Y

Operating System

- Windows 11 Pro
- Windows 10 IoT
- Windows Server 2022
- · Windows Server 2019 IoT
- Ubuntu Linux

Memory

Default 64GB DDR5 (4x16GB) Upgradable

Data Storage

Up to 480TB

RAID

• JBOD 1, 5, 6, 10

RAID Controller

PERC H755

Video Outputs

 Optional NVIDIA Quadro T1000-8GB

I/O Ports

Front ports:

- 1x iDRAC Direct
- 1x USB2.0

Rear ports:

- 1x USB2.0
- 1x USBx3.0
- 1x VGA

Networking

- 6 x 1GbE RJ45 Ports
- 2 x 10GbE SFP+

Security Module

Trusted Platform Module 2.0v3

Hardware Monitoring

iDRAC Enterprise with Now Micro DICE Enhancements Pre-Installed

Warranty

5 year Global Next-Day, Onsite Warranty Standard

Mechanical

Form Factor

2U 24 Bay Rack Server

OS Drives

2 x 480GB M.2 SSD

Data Drives

Up to 24 3.5" SATA Hot Swappable Drives

Power Supplies

Dual 1400W Hot Plug Redundant PSU – 100-240 VAC or 240 VDC

Operating Temperature

50°F to 95°F (10°C to 35°C)

Operating Humidity

10 to 80% (non-condensing)

Dimensions & Weight

- Height 3.41" (86.8mm)
- Width 18.97" (482mm)
- Depth 32.95" (837mm)
- Weight 88lbs max (40.0kg)

