

## because now matters

# **VIGILANT S1000**

SPECIFICATION SHEET

# Optimal for compact installations, with the flexibility to expand

The Vigilant S1000 is a rackmount server that is designed specifically for smaller surveillance deployments. The Vigilant S1000 offers the performance and durability you expect at a price point that is accessible for installations with a limited budget. Additionally, the Now Micro Engineering Team has pre-integrated DICE Management and Monitoring Software. The DICE Complete solution is focused on technical support needs to drive increased first-call resolution and reduced downtime in the field. Hardware information, logs and location information are embedded in a real-time interface that includes KVM, terminal and file system access tools.









**Intel Xeon E-Series Processors** 



Up to 80TB of raw storage



**1U Rackmount Form Factor** 



5-year Next Business Day Onsite Warranty









# **VIGILANT S1000**

## **System**

#### **Processor**

· Intel Xeon E-2324G

## **Operating System**

- Windows 11 Pro
- Windows 10 IoT
- Windows Server 2022
- · Windows Server 2019 IoT
- Ubuntu Linux

## Memory

 Default 16GB DDR4 (2x8GB) Upgradable

## **Data Storage**

Up to 80TB

#### **RAID**

- · Data RAID: Default RAID 5
- · Optional: JBOD, RAID 1

## **RAID Controller**

S150 Software RAID

## **Video Outputs**

- VGA
- · Optional NVIDIA T400 GPU

## I/O Ports

#### Front ports:

- 1x iDRAC Direct
- 1x USB2.0

#### Rear ports:

- 1x USB2.0
- 1x Serial
- 1x USBx3.0
- 1x VGA

## **Networking**

· 2x 1 GbE RJ45 Ports

## **Security Module**

Trusted Platform Module 2.0v3

## **Hardware Monitoring**

- iDRAC Basic with Now Micro DICE Enhancements Pre-Installed
- · Optional iDRAC Enterprise

## Warranty

 5 year Global Next-Day, Onsite Warranty Standard

## Mechanical

## **Form Factor**

• 1U Rackmount Server

### **OS Drive**

• 1 x 240GB M.2 SSD

### **Data Drives**

 Up to 4 3.5" SATA Hot Swappable Drives

## **Power Supplies**

 450 W Bronze 100-240 V AC, cabled

## **Operating Temperature**

• 50°F to 95°F (10°C to 35°C)

## **Operating Humidity**

• 10 to 80% (non-condensing)

## **Dimensions & Weight**

- Height 1.68" (43mm)
- Width 18.97" (482mm)
- Depth 23.45" (596mm)
- Weight 27lbs max (12.2kg)

