

STUDIO P-302

SPECIFICATION SHEET

Powerful, port-dense, dual display capable digital signage device

- Powerful digital signage device, with optional Serial port expansion
- Dual HDMI ports support at stunning visual experience
- ImageSync simplifies setup and configuration, no internet required
- Remote health monitoring and remote access with DICE
- Disaster recovery



HDMI
HIGH-DEFINITION MULTIMEDIA INTERFACE

Key Features



Intel Core processor family



Microsoft Windows 11 Pro



Up to 2 HDMI connections



Optional Serial Ports



3 year depot warranty

STUDIO P-302

System

Processor

- Intel Core Processor Family

Operating Systems

- Windows 10 IoT
- Windows 11 Pro

Memory

2 x SO-DIMMcDDR5, Up to 64GB

Storage

- 1x M.2, 1x 2.5"

RAID

N/A

Connectivity

- LAN: 1x Intel 2.5GB Ethernet, 1x Intel 1 GB Ethernet
- Wireless: Optional

Graphics

Intel UHD Graphics

Video Output

- 1x HDMI 1.4
- 1x HDMI (optional)
- 1x Display Port 1.2

Audio

- Realtek ALC888 Co-Lay ALC897

USB

4x USB 3.2 Gen 2

Ports

Front ports:

- 2 x USB 3.2
- 1 x 3.5mm headphone/mic jack

Rear ports:

- 2 x HDMI TMDS Compatible
- 2 x USB 4 type-C / Thunderbolt 4 / DP 1.4a
- 1 x USB 3.2
- 1 x USB 2.0
- 1 x Intel 2.5 Gb LAN
- 1 x DC power in

Side ports:

- Kensington lock slot

Expandability

2x Serial RS-232 DB9 (optional)

Warranty

3 year depot warranty

Mechanical

Power Supply

150W AC

Mounting

VESA

Dimensions & Weight

- Height – 1.94" (49.28mm)
- Width – 7.44" (188.98mm)
- Depth – 7.13" (181.1mm)
- Weight – 3.1lbs (1.41kg)