

## because now matters

# **VIGILANT S1500**

**SPECIFICATION SHEET** 

## Optimal for compact installations, with the flexibility to expand

The Vigilant S1500 is a rackmount server designed for professional surveillance deployments. Tested, tuned and guaranteed by the Now Micro Engineering Team, The Vigilant S1500 is ready to endure even the toughest installations. Additionally, the Now Micro Engineering Team has pre-integrated DICE Management and Monitoring Software. The DICE Complete solution is focused on technical support needs to drive increased first-call resolution and reduced downtime in the field. Hardware information, logs and location information are embedded in a real-time interface that includes KVM, terminal and file system access tools.









**Intel Xeon E-Series Processors** 



Up to 60TB of raw storage



**1U Rackmount Form Factor** 



5-year Next Business Day Onsite Warranty









# **VIGILANT S1500**

## **System**

#### **Processor**

Intel Xeon E-2324G

## **Operating System**

- · Windows 11 Pro
- Windows 10 IoT
- Windows Server 2022
- · Windows Server 2019 IoT
- Ubuntu Linux

## Memory

Default 16GB DDR4 (2x8GB) Upgradable

#### **Data Storage**

Up to 60TB

#### **RAID**

- Data RAID: Default Raid 5
- · Optional JBOD, 1

### **RAID Controller**

PERC H755

## **Video Outputs**

- VGA
- · Optional NVIDIA T400 GPU

## I/O Ports

#### Front ports:

- 1x iDRAC Direct
- 1x USB2.0

#### Rear ports:

- 1x USB2.0
- 1x Serial
- 1x USBx3.0
- 1x VGA

## Networking

• 2x 1 GbE RJ45 Ports

## **Security Module**

Trusted Platform Module 2.0v3

## **Hardware Monitoring**

iDRAC Basic with Now Micro DICE Enhancements Pre-Installed

Optional iDRAC Enterprise

## Warranty

5 year Global Next-Day, Onsite Warranty Standard

## Mechanical

#### **Form Factor**

1U Rackmount Server

#### **OS Drives**

1 x 240GB M.2 SSD

#### **Data Drives**

Up to 3 3.5" SATA Hot Swappable Drives

## **Power Supplies**

Single 450W Hot Plug Redundant PSU – 100-240 VAC, 50/60 Hz, 4.8 A-2.4 A

## **Operating Temperature**

50°F to 95°F (10°C to 35°C)

## **Operating Humidity**

10 to 80% (non-condensing)

## **Dimensions & Weight**

- Height 1.68" (43mm)
- Width 18.97" (482mm)
- Depth 23.45" (596mm)
- Weight 27lbs max (12.2kg)

