

# because now matters

# VIGILANT W2000

SPECIFICATION SHEET

# Delivers exceptional performance for client viewing applications

The Vigilant W2000 Series, renowned for its versatility, stands out as a top-tier client viewing station. Engineered with multiple features, it seamlessly integrates into diverse installation environments. This dynamic viewing station supports up to four monitors and is specifically designed for mid-range surveillance projects. Powered by the 13th generation Intel Core processor family, it ushers in a new era of computing with an array of cutting-edge features. Additionally, the Now Micro Engineering Team has pre-integrated DICE Management and Monitoring Software. The DICE Complete solution is focused on technical support needs to drive increased first-call resolution and reduced downtime in the field. Hardware information, logs and location information are embedded in a real-time interface that includes KVM, terminal and file system access tools.









13th Generation Intel Core Processors



**Mid Tower Form Factor** 



Supports up to 4 Displays



5-year Global Next Business Day Onsite Warranty









# VIGILANT W2000

# **System**

#### **Processor**

13th Generation Intel i7 Core Processors

# **Operating System**

- Windows 11 Pro
- · Windows 10 IoT

# **Displays Supported**

Up to 4 with NVIDIA GPU

## Memory

Default 16GB DDR5 (2x8GB) Upgradeable to 32GB DDR5

## **Video Outputs**

- · Integrated Intel Graphics
- Optional NVIDIA T400 GPU
- · Optional NVIDIA T1000 GPU

# I/O Ports

Rear ports:

- 2x USB 2.0
- 2x USB 3.2 Type A Gen2
- · 2x USB 3.2 Type A Gen1

# **Networking**

· 2 x 1GbE LAN Ports

# **Security Module**

Trusted Platform Module 2.0v3

## **Hardware Monitoring**

iDRAC Basic with Now Micro DICE Enhancements Pre-Installed Optional iDRAC Enterprise

# Warranty

5 Year Global Next Business Day, Onsite Warranty Standard

# Mechanical

#### Form Factor

**Precision Tower** 

#### **OS Drives**

256GB SSD

## **Power Supplies**

2TB SATA Data Drive Upgradable

## **Operating Temperature**

50°F to 95°F (10°C to 35°C)

## **Operating Humidity**

10 to 80% (non-condensing)

# **Dimensions & Weight**

- Height 14.52" (369mm)
- Width 6.81" (173mm)
- Depth 16.53" (420mm)
- Weight 18.74 lbs (8.5 kg)

